

Page: 1/10

Printing date: 23 February 2018 Revision: 23 February 2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: Rapid Refloor XP Part B ISO
- · Product code: No other identifiers
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture:

Component of a Control Joint Polyurethane System. Caulking and Sealing.

- · Uses advised against: No further relevant information available.
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

METZGER/McGUIRE

Mailing Address:

PO Box 2217

Concord, NH 03302

Shipping Address:

807 Route 3-A

Bow, NH 03304

Phone: 603-224-6122

Toll Free: 800-223-6680

Email: info@metzgermcguire.com

· Importer / Distributor:

DR. Schulze GmbH

Bollenberg 10

D-57234 Wilnsdorf

+49 (0) 2737/5953-0

· 1.4 Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Cont'd. on page 2)



Page: 2/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 1)

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

4,4'-methylenediphenyl diisocyanate

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

· Additional information:

Restricted to professional users.

- · 2.3 Other hazards There are no other hazards not otherwise classified that have been identified.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

l	<u></u>				
	· Components:				
	CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	80-95%		
Н	EINECS: 202-966-0	& Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373			
	Index number: 615-005-00-9	↑ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;			
	Reg.nr.: 01-2119457014-47-XXXX	Skin Sens. 1, H317; STOT SE 3, H335			
ΙĪ	CAS: 108-32-7	propylene carbonate	5-20%		
	EINECS: 203-572-1	① Eye Irrit. 2, H319			
Н	Index number: 607-194-00-1				
	Reg.nr.: 01-2119537232-48-XXXX				

· Additional information: For the wording of the listed Hazard Statements refer to section 16.



Page: 3/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure to call for a doctor.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Asthma attacks

Breathing difficulty

Coughing

Dizziness

Allergic reactions

May cause respiratory irritation.

Irritating to eyes, respiratory system and skin.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

· Hazards:

Danger of impaired breathing.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

Contains isocyanates. Consult literature for specific antidotes.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Cont'd. on page 4)



Page: 4/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 3)

5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

· Additional information: Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Isolate area and prevent access.

· 6.2 Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidisers, strong acids, strong bases.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from humidity and water.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

(Cont'd. on page 5)



Page: 5/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 4)

· Ingredients with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

WEL (Great Britain) Short-term value: 0,07 mg/m³

Long-term value: 0,02 mg/m³

Sen; as -NCO

- · **DNELs:** No further relevant information available.
- · PNECs: No further relevant information available.

· 8.2 Exposure controls

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid breathing mist/vapours/spray. Avoid contact with the eyes and skin.

· Respiratory protection:



Combined Organic Vapour and Particulate Respirator is recommended for use during all processing activities.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment:

No further relevant information available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· Appearance

Form: Liquid Yellow
• Odour: Aromatic

· Odour threshold: Not determined.

· pH-value: Not determined.

• Melting point/freezing point: 5-20 °C

(Cont'd. on page 6)



Page: 6/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

	(Cont'd. from page		
· Initial boiling point and boiling range: >200 °C			
· Flash point:	>200 °C (Pensky-Martens Closed Cup)		
· Flammability (solid, gas):	Not applicable.		
· Auto/Self-ignition temperature:	Not determined.		
· Decomposition temperature:	Not determined.		
· Explosive properties:	Product does not present an explosion hazard.		
Explosion limitsLower:Upper:Oxidising properties	Not determined. Not determined. Not determined.		
· Vapour pressure at 25 °C:	<0,0001 mm Hg		
 Density: Relative density at 20 °C: Vapour density: Evaporation rate: 	1.2 g/cm³ Not determined. Not determined.		
 Solubility in / Miscibility with water: 	Slowly reacts with water.		
· Partition coefficient: n-octanol/water:	Not determined.		
· ViscosityDynamic:Kinematic:· 9.2 Other information	Not determined. Not determined. No further relevant information available.		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under normal temperatures and pressures.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with strong oxidising agents.

Exothermic reaction.

- · 10.4 Conditions to avoid Excessive heat.
- · 10.5 Incompatible materials Oxidisers, strong bases, strong acids
- · 10.6 Hazardous decomposition products

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Hydrogen cyanide (prussic acid)

Isocyanate



Page: 7/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 6)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

Harmful if inhaled.

· LD/LC50 values relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- Primary irritant effect
- Skin corrosion/irritation:

Causes skin irritation.

· Serious eye damage/irritation:

Causes serious eye irritation.

· Respiratory or skin sensitisation:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Probable routes of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Harmful if inhaled.

Irritating to eyes, respiratory system and skin.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Suspected of causing cancer.

- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure:

May cause respiratory irritation.

· STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Cont'd. on page 8)



Page: 8/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 7)

· 12.5 Results of PBT and vPvB assessment

- PBT: Not applicable.vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information		
· 14.1 UN-Number · DOT, ADR, IMDG, IATA	Not Regulated	
· 14.2 UN proper shipping name · DOT, ADR, IMDG, IATA	Not Regulated	
· 14.3 Transport hazard class(es)		
· DOT, ADR, IMDG, IATA · Class	Not Regulated	
· 14.4 Packing group · DOT, ADR, IMDG, IATA	Not Regulated	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to An of Marpol and the IBC Code	nex II Not applicable.	
· Transport/Additional information:		
· ADR · Transport category	4	



Page: 9/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 8)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients are listed.
- · National regulations:
- · Water hazard class: Water hazard class 1: slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

LDLo: Lowest Lethal Dose Observed

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

(Cont'd. on page 10)



Page: 10/10

Printing date: 23 February 2018 Revision: 23 February 2018

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. from page 9)

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com